



Classe C

CLD

Clapeta de dozaj circulara motorizabila



TIP
Circular
Tot sau putin



APLICATIE
Dozaj



DIMENSIUNI
100 la 710 mm



ETANSEITATE
Clapeta clasa 4
Carcasa clasa C



COMANDA
Motorizabila



ACCES PRODUS ON LINE



Classe C

CRT

Clapeta de dozaj etansa cu inchidere totala



TIP
Circular
Tot sau nimic



APLICATIE
Dozaj
Isolare



DIMENSIUNI
100 la 630 mm



ETANSEITATE
Garnituri
de racordare
Clapeta clasa 4
Carcasa clasa C



COMMANDE
Motorizabila



ACCES PRODUS ON LINE

AVANTAJE

- Robust.
- Etanseitatea clapetei clasa 4 / EN 1751.
- Etanseitatea carcasei : classe C in presiune si in depresiune conform EN 1751.
- Clapeta motorizabila (motor optional).
- Versiune Atex posibila, pentru zone 1/21 ou 2/22.

APLICARE / UTILIZARE

- Echilibrarea retelelor aeraulice.
- Isolarea unei conducte de celelalte.
- Utilizare pentru ventilatie, incalzire sau aer conditionat.
- Comanda manuala propusa separat (R10 ou R12).
- CLD inox : constructia speciala, a ne consulta.


CONSTRUCTIE / COMPOZITIE

- Carcasa si lama din otel galvanizat.
- Livrat fara garnitura de etanseitate pe partea exteriora.

DESCRIERE TEHNICA

• Dimensiuni

mm	Clapeta CLD		
	Ø 100 la Ø 315	Ø 355	Ø 400 la Ø 710
L	199	300	400
Ax	patrat 10 x 10	circular ØD= 12	circular ØD= 12
Comanda	R10		R12
A	60		100



AVANTAJE

- Robust
- Etanseitatea clapetei clasa 4 conform EN 1751.
- Etanseitatea carcasei : classe C in presiune si in depresiune conform EN 1751.
- Garnituri exteriora.
- Livrat cu un maner.
- Clapeta motorizabila (motor optional).

APLICARE / UTILIZARE

- Echilibrarea retelelor aeraulice.
- Isolarea unei conducte de celelalte.
- Utilizare pentru ventilatie, incalzire sau aer conditionat.

CONSTRUCTIE / COMPOZITIE

- Carcasa si lama din otel galvanizat.
- Livrat cu garnitura de etanseitate pe partea exteriora si maner de comanda
- Disponibil in inox

DESCRIERE TEHNICA

• Dimensiuni

Ø d (mm)	A (mm)	M (mm)	H (mm)
100	199	23	28
125	199	23	34
160	199	23	38
200	199	23	41
250	199	23	43
315	199	23	44
400	255	25	80
500	255	25	80
630	255	25	80

